



EC DECLARATION OF CONFORMITY

The undersigned, representing the

Puidukoda OÜ

and its manufacturing plant

in Karksi, Estonia

herewith declares that the

Solid wood panelling and cladding

is in conformity with the provisions of the EC Directive 89/106/EEC (Construction Products Directive – CPD), and that Annex ZA of

EN 14915:2006

has been applied.

The provisions to which the product conforms are given on the reverse side of this declaration.

Karksi 20.05.2010

Enn Kinnas Chairman of the Board

Characteristic	Performance declaration
Species	Spruce (<i>Picea abies</i>); Pine (<i>Pinus sylvestris</i>);
	Siberian Larch (<i>Larix Sibirica</i>)
Growth area	Extended Nordic growth area
Range of thickness	9 – 100 mm
Range of width	40 – 250 mm
Range of length	More than 2,0 m
Surface finish	Sawn and planed
Intended use	For internal and external use
Mean density	400 – 700 kg/m ³
Water vapour permeability	50 – 90 μ (Wet cup)
Content of pentachlorophenol	No PCP release
Release of formaldehyde	Class E1
Sound absorption	0,1/0,3
Thermal conductivity	0,11 – 0,18 W/m K
Biological durability	Class 4 (Picea abies), Class 3 – 4 (Pinus sylvestris),
	Class 3 (Larix Sibirica)
Reaction to fire	D-s2, d0